

# SOFTJET PLUS

PRINT FLAGS  
DIGITALLY WITH

SOFTJET PLUS, the 2.5mtrs entry level printer is the perfect solution for minimum investment and maximum profitability. A soft signage printer, Softjet Plus is an ideal machine for Flag printing. It is not just environment-friendly but also extremely friendly on the pocket. Flag off success with Softjet Plus.



**MAXIMUM  
APPLICATIONS**  
MAXIMUM BUSINESS SPREAD

## SPECIFICATIONS

SOFTJET PLUS				
<b>Models</b>		<b>M4412</b>		
Printing Technology		Drop on demand, Piezo Electric inkjet		
Print Heads		Industrial Grade Jetting Assemblies		
No. of Print Heads		4		
Fabrics	Width	2600 mm		
	Thickness	Maximum 10 mm with Liner		
	Roll Outer Diameter	Maximum 300 mm		
	Roll Weight	Maximum 90 kgs		
	Core Diameter	76.2 mm		
Types		Polyester, Satin, Canvas & Blends		
Printing Width		Maximum 2500 mm		
Inks	Types	Direct disperse inks		
	Colors	4 Colors		
Printing Resolution (dots per inch)		Maximum Up to 1440 dpi		
Distance Accuracy		Error of less than $\pm 0.3\%$ of distance travelled, or $\pm 0.3$ mm, whichever is greater		
Media Heating System		Pre-heater and post-heater, setting range for the preset temperature: 30 to 60 C. Dryer setting range for the preset temperature : 30 to 60°C		
Connectivity		High Speed USB		
Power Requirements		AC 220 V $\pm 10\%$ , 20 A, 50/60 Hz		
Dimensions ( Printer only)		4500 mm x 1150 mm x 1640 mm (LxWxH)		
RIP software		PhotoPrint (ColorJet Edition)		
Weight (approx. with stand)		1650 Kgs		
Environmental	Power ON	Temperature: 18°C to 28°C. Humidity: 35% to 80%RH (non-condensing)		
	Power OFF	Temperature: 5°C to 40°C. Humidity: 20% to 80%RH (non-condensing)		
<b>Modes</b>	<b>Print DPI</b>	<b>Passes</b>	<b>Speed (In Sq. mtr/hr)</b>	<b>Speed (In Sq. feet/hr)</b>
Mode 1	720 x 540	3	46	495
Mode 2	720 x 720	4	30	323
Mode 3	720 x 1080	6	23	248
Mode 4	720 x 1440	8	15	162